


Female Disconnects, Fully Insulated, Nylon

- Funnel Entry
- Internal Wire Stop
- Insulation Support
- Standard Receptacle Housings




*UL/CSA standards do not exist for .110" X .010" receptacles.
**UL with 17 AWG wire.

PANDUIT® Part Number	Wire Range	Color Code	Max. Ins.	Dimensions (In.)			Tab Size In. (mm)	CA9 Series Crimp Die	CA-800 Series Crimp Die	Pcs. Per Reel
				A	W	H				
DNF18-110FIB-3K	22-18 .010 Stock	Red	.120	.71	.19	.15	.110 X .032 (2.8 X .8)	CD9-7A	CD-800-7	3000
DNF18-111FIB-3K		Red		.71	.19	.15	.110 X .020 (2.8 X .5)			3000
DNF18-112FIB-3K		Natural		.71	.19	.15	.110 X .010 (2.8 X .3)			3000
DNF18-187FIB-3K	22-18 .016 Stock	Red	.135	.78	.29	.16	.187 X .032 (4.8 X .8)	CD9-4A	CD-800-4	3000
DNF18-188FIB-3K				.78	.29	.16	.187 X .020 (4.8 X .5)			3000
DNF18-205FIB-3K				.78	.31	.22	.187/.205X.032 (4.8/5.2 X .8)			3000
DNF18-206FIB-3K				.78	.31	.22	.187/.205X.020 (4.8/5.2 X .5)			3000
DNF18-250FIB-3K				.84	.35	.22	.250 X .032 (6.3 X .8)			3000
DNF14-187FIB-3K	16-14 .016 Stock	Blue	.158	.78	.29	.18	.187 X .032 (4.8 X .8)	CD9-5A	CD-800-5	3000
DNF14-188FIB-3K				.78	.29	.18	.187 X .020 (4.8 X .5)			3000
DNF14-205FIB-3K				.78	.31	.22	.187/.205X.032 (4.8/5.2 X .8)			3000
DNF14-206FIB-3K				.78	.31	.22	.187/.205X.020 (4.8/5.2 X .5)			3000
DNF14-250FIB-3K				.84	.35	.22	.250 X .032 (6.3 X .8)			3000
DNF10-250FIB-2K	12-10 .018 Stock	Yellow	.220	.96	.35	.23	.250 X .032 (6.3 X .8)	CD9-13B	CD-800-13	2000
DNF18205FIBX-2K	22-18 .016 Stock	Red	.210	.87	.31	.22	.187/.205X.032 (4.8/5.2 X .8)	CD9-6B	CD-800-6	2000
DNF18206FIBX-2K				.87	.31	.22	.187/.205X.020 (4.8/5.2 X .5)			2000
DNF18250FIBX-2K				.93	.35	.22	.250 X .032 (6.3 X .8)			2000
DNF14205FIBX-2K	16-14 .016 Stock	Blue	.240	.87	.31	.22	.187/.205X.032 (4.8/5.2 X .8)	CD9-8B	CD-800-8	2000
DNF14206FIBX-2K				.87	.31	.22	.187/.205X.020 (4.8/5.2 X .5)			2000
DNF14250FIBX-2K				.93	.35	.22	.250 X .032 (6.3 X .8)			2000


Order number of pieces required, in multiples of standard reel quantity.
Prime items appear in **BOLD**.

- Expanded Wire Entry Area for Large Wire Insulation O.D.



Right Angle, Female Disconnects, Nylon Fully Insulated



- Funnel Entry
- Insulation Support



PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Dimensions (In.)				Tab Size In. (mm)	CA9 Series Crimp Die	CA-800 Series Crimp Die	Pcs. Per Reel
				A	X	W	H				
DNFR18205FIB-KD	22-18 .018 Stock	Red	.178	.57	.60	.37	.21	.187/.205 X .032 (4.8/5.2 X .8)	CD9-9C	CD-800-9	1500
DNFR18206FIB-KD				.57	.60	.37	.21	.187/.205 X .020 (4.8/5.2 X .5)			1500
DNFR18250FIB-KD				.57	.60	.37	.21	.250 X .032 (6.3 X .8)			1500
DNFR14205FIB-KD	16-14 .018 Stock	Blue	.178	.57	.60	.37	.21	.187/.205 X .032 (4.8/5.2 X .8)	CD9-9C	CD-800-9	1500
DNFR14206FIB-KD				.57	.60	.37	.21	.187/.205 X .020 (4.8/5.2 X .5)			1500
DNFR14250FIB-KD				.57	.60	.37	.21	.250 X .032 (6.3 X .8)			1500

Order number of pieces required, in multiples of standard reel quantity. Prime items appear in **BOLD**.

- Funnel Entry
- Plastic Insulation Crimp
- Internal Wire Stop



Barrel Insulated, Female Disconnects, Vinyl Insulated

PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Dimensions (In.)		Tab Size In. (mm)	CA9 Series Crimp Die	CA-800 Series Crimp Die	Pcs. Per Reel
				A	W				
DV18-187B-3K	22-18 .016 Stock	Red	.160	.77	.23	.187 X .032 (4.8 X .8)	CD9-1A	CD-800-1	3000
DV18-188B-3K				.77	.23	.187 X .020 (4.8 X .5)			3000
DV18-205B-3K				.77	.25	.187/.205 X .032 (4.8/5.2 X .8)			3000
DV18-206B-3K				.77	.25	.187/.205 X .020 (4.8/5.2 X .5)			3000
DV18-250B-3K				.83	.29	.250 X .032 (6.3 X .8)			3000
DV14-187B-3K	16-14 .016 Stock	Blue	.170	.77	.23	.187 X .032 (4.8 X .8)	CD9-2A	CD-800-2	3000
DV14-188B-3K				.77	.23	.187 X .020 (4.8 X .5)			3000
DV14-205B-3K				.77	.25	.187/.205 X .032 (4.8/5.2 X .8)			3000
DV14-206B-3K				.77	.25	.187/.205 X .020 (4.5/5.2 X .5)			3000
DV14-250B-3K				.83	.29	.250 X .032 (6.3 X .8)			3000
DV10-250-2K	12-10 .018 Stock	Yellow	.230	.95	.29	.250 x .032 (6.3 x .8)	CD9-3B	CD-800-3	2000
DV10-250C-2K				.220	.95	.29			.250 X .032 (6.4 X .8)

LISTED* 20H3 CERTIFIED*
* Except DV10-250-2K
Prime items appear in **BOLD**.

‡Compressor tab disconnect to fit .250" tabs with a post style support. Order number of pieces required, in multiples of standard reel quantity.

For complete product and specification information visit our website at: www.panduit.com/eg or call: 800-777-3300

Sold exclusively through authorized PANDUIT distributors.