





### 1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier

<p><b>SOD123W</b></p> 	<p><b>Voltage</b> 200 V</p>	<p><b>Current</b> 1.0 A</p>	
	<p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• Top-Glass Technology</li> <li>• Low profile package</li> <li>• Ideal for automated placement</li> <li>• Low power losses, high efficiency</li> <li>• High surge current capability</li> <li>• Cavity-free glass-passivated junction</li> <li>• Low forward voltage drop</li> <li>• Solder dip 260°C, 10s</li> <li>• Component in accordance to RoHS 2011/65/EU and WEEE 2002/96/EC</li> <li>• Meets MSL level 1, per J-STD-020, LF maximum peak of 260° C</li> <li>• Very soft recovery characteristics</li> <li>• Significantly reduced EMI. Very low Noise.</li> </ul>		   <b>RoHS COMPLIANT</b>
	<p><b>MECHANICAL DATA</b></p> <ul style="list-style-type: none"> <li>• <b>Case:</b> SOD123W. Epoxy meets UL 94V-0 flammability rating.</li> <li>• <b>Polarity:</b> Color band denotes cathode end.</li> <li>• <b>Terminals:</b> Matte tin plated leads, solderable per MIL-STD-750 Method 2026, J-STD-002 and JESD22-B102. Consumer grade, meets JESD 201 class 1A whisker test. HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test.</li> </ul>		
<p><b>TYPICAL APPLICATIONS</b></p> <p>Used in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer, automotive and telecommunication.</p>			

### Maximum Ratings and Electrical Characteristics at 25 °C

		FES1DWSR TG
Marking Code		WF
$V_{RRM}$	Maximum Recurrent Peak Reverse Voltage (V)	200
$V_{RMS}$	Maximum RMS Voltage (V)	140
$V_{DC}$	Maximum DC Blocking Voltage (V)	200
$I_{F(AV)}$	Maximum Average Forward Rectified Current @ $T_C = 110\text{ °C}$	1.0 A
$I_{FSM}$	Peak Forward Surge Current, 8.3 ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	50 A
$V_F$	Maximum Instantaneous Forward Voltage @ 1.0A	$T_j = 25\text{ °C}$ 0.90 V $T_j = 100\text{ °C}$ 0.75 V
$I_R$	Maximum DC Reverse Leakage Current. $V_R = V_{RRM}$	$T_j = 25\text{ °C}$ 5 $\mu$ A $T_j = 100\text{ °C}$ 10 $\mu$ A $T_j = 175\text{ °C}$ 100 $\mu$ A
$C_j$	Typical Junction Capacitance (1MHz; -4V)	15 pF
$R_{th(j-c)}$ $R_{th(j-a)}$	Typical Thermal Resistance (5x5 mm <sup>2</sup> x 130 $\mu$ Copper Area)	27 °C/W 75 °C/W
$T_j - T_{stg}$	Operating Junction and Storage Temperature Range	-65 to + 175 °C

### 1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier

#### Recovery Characteristics ( $T_j = 25\text{ }^\circ\text{C}$ )


Symbol	Test Conditions	Min.	Max.	Typ.	Unit
trr	$I_F = 0.5\text{ A}$ , $dI_F/dt = 100\text{ A}/\mu\text{s}$ , $I_{RR} = 1000\text{ mA}$		25		ns
ta				15	
tb				6	
tb/ta	Softness	0.45			
Qrr	$VR = 30\text{V}$ , $dI_F/dt = 50\text{A}/\mu\text{s}$ , $I_F = 1\text{A}$			7	nC
	$VR = 30\text{V}$ , $dI_F/dt = 50\text{A}/\mu\text{s}$ , $I_F = 2\text{A}$			8.5	
	$VR = 30\text{V}$ , $dI_F/dt = 50\text{A}/\mu\text{s}$ , $I_F = 5\text{A}$			9.5	
	$VR = 30\text{V}$ , $dI_F/dt = 50\text{A}/\mu\text{s}$ , $I_F = 15\text{A}$			10	
Qrr	$VR = 30\text{V}$ , $dI_F/dt = 150\text{A}/\mu\text{s}$ , $I_F = 1\text{A}$			9	nC
	$VR = 30\text{V}$ , $dI_F/dt = 150\text{A}/\mu\text{s}$ , $I_F = 2\text{A}$			15	
	$VR = 30\text{V}$ , $dI_F/dt = 150\text{A}/\mu\text{s}$ , $I_F = 5\text{A}$			25	
	$VR = 30\text{V}$ , $dI_F/dt = 150\text{A}/\mu\text{s}$ , $I_F = 15\text{A}$			30	

**1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier**

**Ordering information**


PREFERRED P/N	PACKAGE CODE	DELIVERY MODE	BASE QUANTITY	UNIT WEIGHT (g)
FES1DWSR TG TRTB	TRTB	13" diameter tape and reel	10,000	0.0196
FES1DWSR TG HE3 TRTB	TRTB	13" diameter tape and reel	10,000	0.0196

**Package Outline Dimensions: (mm) SOD123W**




### 1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier


**Fig. 1 REVERSE CURRENT vs REVERSE VOLTAGE**




**Fig. 2 FORWARD VOLTAGE vs FORWARD CURRENT**




**Fig. 3 LOW FREQUENCY POWER LOSSES vs. AVERAGE CURRENT**




**Fig. 4 PEAK CURRENT vs. FORM FACTOR**



**Fig. 5 FORWARD CURRENT DERATING CURVE**




**Fig. 6  $tb/ta$  CURVES vs. FORWARD CURRENT**




### 1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier


**Fig. 7  $t_{rr}$ ,  $t_a$  AND  $t_b$  CURVES vs FORWARD CURRENT.**  
 $T_c = 25^\circ C$




**Fig. 8  $t_{rr}$ ,  $t_a$  AND  $t_b$  CURVES vs FORWARD CURRENT.**  
 $T_c = 100^\circ C$




**Fig. 9 RECOVERY TIME vs  $dI_F/dt$**




**Fig. 10 PEAK REVERSE CURRENT vs  $dI_F/dt$**



**Fig. 11  $t_{rr}$  vs  $dI_F/dt$ .  $I_F = 2 A$**




**Fig. 12  $t_{rr}$  vs  $dI_F/dt$ .  $I_F = 0.1 A$**




**1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier**


**Fig. 13 trr vs  $di_F/dt$ .  $I_F = 0.5 A$**




**Fig. 14 QRR vs JUNCTION TEMPERATURE**




**Fig. 15 IRM vs JUNCTION TEMPERATURE**




**Fig. 16 trr vs JUNCTION TEMPERATURE**



**Fig. 17 TRANSIENT PEAK FORWARD VOLTAGE vs  $di_F/dt$**




**Fig. 18 FORWARD RECOVERY TIME vs  $di_F/dt$**




**1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier**

**Fig. 19 RECOVERY TIME vs JUNCTION TEMPERATURE**



**Fig. 20 JUNCTION CAPACITANCE vs. REVERSE BIAS**



**1.0 Amp. Surface Mount Top Glass Passivated Ultrafast Very Soft Recovery Rectifier**

## Disclaimer

All product, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.

Fagor Electrónica, S.Coop., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Fagor"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Fagor makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Fagor disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Fagor's knowledge of typical requirements that are often placed on Fagor products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Fagor's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Fagor products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Fagor product could result in personal injury or death. Customers using or selling Fagor products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Fagor and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Fagor or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Fagor personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Fagor, Product names and markings noted herein may be trademarks of their respective owners.